



IDEALFLUIDS

SETTING BENCHMARKS

M.R.O. SPECIALTY CHEMICALS



OX-PRO 426 Acid Cleaner

PRODUCT DESCRIPTION

Ox-Pro 426 Rust and cement remover effectively removes rust, scales and stains from steel, ceramic and wooden surfaces. Its additives are carefully selected to provide good wetting profile, corrosion inhibition and descaling properties. An acid based cleaner and metal brightener that is used to remove light rust, rust stains, and inhibits corrosion. Ox-Pro 426 will leave a light passivation layer on metal surfaces.

APPLICATION

Cleaning Application

Always add Ox-Pro 426 to water, never the reverse. Product should always be used in a plastic bucket/ container. Remove rust flakes, oil, grease and other dirt prior to using Ox-Pro 426.

Use a solution of 50% to neat for severely corroded surfaces. Rinse off surface with water after 15-30 minutes.

Use a solution of 20—50% for less corroded or soiled surfaces and tarnishes on copper and brass. Rinse off surface after 15-30 minutes.

Use a solution of 10-30% on aluminium. Rinse with water after a maximum of 5 minutes.

Use a solution of 10-30% for removal of rust stains on painted surfaces. Rinse off with water 15-20 minutes after application.

Apply 50% solution for removal of light cement stains and lime. High pressure wash after 30-40 minutes, and for solidified cement, use Ox-Pro 421.

Cleanup

Wash down with freshwater after cleaning. Rinse tools/equipment immediately after use with freshwater.

www.idealfluids.com

CHARACTERISTICS

Ox-Pro 426 Cement & Rust remover is:

- Rust remover for ferrous metals
- Provides a passivation layer for ferrous metal
- Preparation of aluminium surfaces before anodizing, painting and electroplating.
- Oxide removal of brass, bronze, copper, zinc, magnesium and magnesium alloys
- Brightener for aluminium and copper
- Scale remover for bathroom tubs, showers and pipes.

PHYSICAL PROPERTIES

Appearance : Colourless to yellow liquid

Specific Gravity : 1.2 ± 0.05 @20oC

pH : 1.0 ± 0.5

Flash Point : Not applicable

Solubility : Miscible in water

Packing : 5 liters pail, 25 liters drum; 200L drums, 1000L IBC



Contact our customer service today!

Email: sales@idealfluids.com

Contact No. (+65) 9296 7002

www.idealfluids.com

Contact our customer service
today!
Email: sales@idealfluids.com
Contact No. (+65) 9296 7002